



TERRAMAC® RT14 RUBBER TRACK CARRIER

Standard RT14 Specs

The Terramac® RT14 features a 28,000 lb. carrying capacity and is sure to get noticed for its ability to tackle the heavy loads. Customizable attachments available, contact your local Dealer or Terramac® factory for more details.



DIMENSIONS	
Full Length	19' 11"
Full Width	9' 10"
Wheel Base	12' 5"
Min Ground Clearance	23"
Front Overhang	3' 1.5"
Track Width	31.5"
Track Length	15' 1"
Full Height	10' 4"
Height of Rock Bed	6' 6"
Height of Rock Bed Side (Vessel)	19"
Length of Rock Bed (Vessel)	11' 5"
Width of Rock Bed (Vessel)	8' 12"
Dumping Angle	60°
Machine Weight (with bed)	32,650 lbs.

ENGINE	
Manufacturer	Cummins
Model	QSB 8.3
Displacement	506 cu. in.
Horsepower	280 HP
Electrical System	12 VDC
Battery	8D with 1400 CCA
Fuel Capacity	60 gallons

HYDRAULICS	
Transmission	HST
Piston Pump Capacity (x2)	64 gpm / side
Relief Valve Piston Pump	5,500 PSI
Tandem Gear Pump Capacity	
Front Section (HST Drive)	22.5 gpm @ 500 PSI
Rear Section (Aux Output)	16 gpm @ 2500 PSI

PERFORMANCE	
Max. Carrying Capacity	28,000 lbs.
Travel Speed - 1st Gear	2.8 mph
Travel Speed - 2nd Gear	5.9 mph
Gradability (unloaded)	32%
Turning Radius	10' 6"
Ground Pressure (full capacity)	7.5 PSI
Ground Pressure (unloaded)	3.9 PSI

11/2015

TERRAMAC[®] RT14 RUBBER TRACK CARRIER

Standard RT14 Units & Dimensions

